



Scotchcal™ Opaque Graphic Film

Series 80

Product Bulletin

Product Description

These excellent cast films are a range of colored films that have been specially developed to be knife cut on electronic systems. The film range is available in 84 colors including 8 metallic tones.

Series 80 films have good conformability for application on flat or moderate curved surfaces, with or without rivets.

They are excellent for easy cutting of small letters or complex graphics.

The colorless adhesive ideally suits this material for use on windows or other transparent substrates.

Product Line	Electrocut	SC80-X	X = color code, opaque, glossy (and few matte), permanent adhesive Wide selection out of large color range. Special colors available on request
--------------	------------	--------	--

Product Characteristics

These are typical values for unprocessed products.

Contact your 3M representative for a custom specification.

Physical & Application	Material	cast vinyl	
	Surface finish	glossy and matte (see product line)	
	Thickness (film)	50 µm (0.05 mm)	
	Adhesive type	solvent acrylic; pressure-sensitive	
	Adhesive appearance	clear	
	Liner	Kraft paper	
	Notice!	weight of Kraft paper is 120 g/m ² .	
	Adhesion	20 N/25 mm	FTM 1: 180° peel, substrate: glass; cond: 24 h 23°C/50%RH
	Application method	wet or dry	
	Applied shrinkage	< 0.2 mm	FTM 14
	Application	+8°C minimum (air and substrate)	
	Service temperature	-40°C to +95°C	
	Surface type	flat to curved, incl. rivets	
	Substrate type	aluminum, glass, PMMA, PC*, ABS, paint PC*: Polycarbonates might require drying with heat before use	
	Graphic removal	Fair to remove with heat and/or chemicals from supported substrates.	
		No liability is given for ease or speed of removal of any graphic. Pay attention to adequate air and substrate temperature.	

Durability Unprocessed film The following durability data are given for unprocessed film only!

Graphic durability is largely determined by the climate and the angle of exposure. Find below a table showing the durability of a product according to the angle of exposure and the geographical location of the application.

Vertical outdoor exposure	Northern Europe	Mediterranean area	Africa & Gulf area
white/black	10 years	8 years	6 years
colours	8 years	6 years	4 years
transparent	8 years	6 years	4 years
metallics	4 years	3 years	2 years

Definitions Vertical: face of graphic $\pm 10^\circ$ from vertical
Interior: application in-side a building without direct exposure to sunlight

Storage Shelf life 2 years from the date on the original box
Up to 2 years unprocessed, or
processed within 1 year and apply within 1 year of processing

Storage conditions! 4°C to 40°C, out of sunlight, original container in clean and dry area.

Flammability Flammability standards are different from country to country. Ask your local 3M contact for details, please.

Limitations of End Uses

3M specifically does not recommend or warrant the following uses, but please contact us to discuss your needs to recommend other products.

Graphic applied to

- flexible substrates incl. Panaflex™ and Panagraphics™.
- low surface energy substrates or substrates with low surface energy coating.
- other than flat or moderate curved/corrugated surfaces.
- painted or unpainted wallboards, gypsum boards and wallpapers.
- stainless steel.
- surfaces not clean and more than moderate textured.
- surfaces with poor paint to substrate adhesion.

Graphic removal from - signs or existing graphics that must remain intact.

Graphic subjected to - gasoline vapors or spills.

Important Notice

- 3M Commercial Graphics Division products are not tested against automotive manufacturer specifications!
- Non vertical applications will have a significant decrease in durability!
- Thermoforming of applied film is not recommended!
- 3M accepts no liability for glass breakage when using this film for window graphics.

Graphics Manufacturing

- Shipping finished graphics Flat, or rolled film side out on 130 mm (5 inch) or larger core. These methods help to prevent the liner from wrinkling or application tape, if used, from popping off.
- Color appearance of metallic films Due to the metallic effect, the color appearance of the film is dependent on the viewing angle to the product!
All metallic films of one color should be processed out of one lot of material. The job design should be done that all parts are applied the same orientation.

Converting Information

Based upon cutting evaluations the minimum height for text is 10 mm using upper and lowercase Helvetica Medium. The stroke width should not be lower than 1 mm.

Electronic Cutting

The variable characteristics of electronically controlled cutting equipment require users to verify their specific requirements.

- Sharpness of knife blade Dull blades impart a serrated look to the edge of the cut film.
- Weight of knife blade The ideal weight slightly scores the liner. Too little weight does not cut completely through the film and the adhesive. Excessive weight cuts the liner and causes the blade to drag, accelerating wear and creating a serrated cut edge on the film.
- Weeding The excess film should be weed (removed) as soon after cutting as practical. This is to minimize the effect of possible adhesive flow.
- Temperature and relative humidity Temperature and relative humidity are minor considerations, but avoid extreme or rapid fluctuating conditions.
- Roll storage Store the film in the same environment as the cutting equipment.
- Further information For more details refer to our instruction bulletin 4.1 'Sheeting, Scoring, Film Cutting', please
[>Instruction Bulletin 4.1'Sheeting, Scoring, Film cutting'<](#)

Maintenance and Cleaning

Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without strong solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline.)
Refer to Instruction Bulletin 6.5 'storage, handling, maintenance and removal of films and sheetings', for general maintenance and cleaning information.

[>Instruction Bulletin 6.5 'Storage, Handling, Maintenance and Removal of Films and Sheetings'<](#)

Remarks

This bulletin provides technical information only.

Important notice

All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.
Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Additional Information

Visit the web site of your local subsidiary at www.3m.eu/graphicsolutions for getting more:

- details about 3M™ MCS™ Warranty and 3M™ Performance Guarantee
- additional instruction bulletins
- a complete product overview about materials 3M is offering

3M Europe S.A./N.V.
Hermeslaan 7
1831 Diegem, Belgium

Responsible for this technical bulletin
3M Deutschland GmbH | Display & Graphics Laboratory
Carl-Schurz-Str. 1 | 41453 Neuss, Germany

3M, Controllac, Scotchcal, Comply and MCS are trademarks of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.